LED FLOOD LIGHT

# HI-807

## Himalaya Stadium Flood Light



AVAILABLE WATTAGE

120W | 250W | 350W | 500W | 600W | 700W | 1000W | 1200W | 1500W | 2000W

TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Efficacy | Up to 200 lm/W |
| Power factor | > 0.90 |
| Input | AC 85–300V @ 50Hz |
| Operating temperature | -10°C to 50°C |
| Surge protection | 6KV internal and 10KV external |
| Ingress protection | IP66 (water & dust resistant) |
| Material | Aluminium |
| Beam angle | 25° / 60° / 90° |
| Protection | Over-voltage protection (auto cut-off above 320V), short-circuit protection, over-temperature protection |
| CCT | 3K / 6K |
| Warranty | 2 years |

Precision optical configurations for project-specific stadium lighting. Multiple beam angle options.

- Manufactured by Hitvika Industries, Gandhinagar
- Dealer, contractor and project pricing
- Custom wattage, colour and OEM branding on request
- Datasheet and samples available on request

HITVIKA INDUSTRIES
B-202/203, Sector-25, Electronics GIDC
Gandhinagar, Gujarat 382024, India

CONTACT
+91 97247 48250
sales@hitvikaindustries.com
hitvikaindustries.com